

N° LED	W	Lm to the light source				R / V / B		
168	14	1100	24V	IP40	DIFFUSE	-	-	2700K 3000K 4000K

Model	Description	Dimensions Ø500mm x 70mm
	On-wall Led light body with double emission. Circular light diffuser in finely worked stone. It is provided with 50cm cable for the electrical connection by power supply. Indoor installation on any rigid surface. Fixing by two screws maximum diameter 6mm, on expansion plug (example Fischer) not supplied by us. Finish: finely worked Trani's Beige stone "Tracce Beige".	

Trace the screws position	Carry out holes for screws' wall plugs	Carry out electrical connections and fix the support	Fix the first and the largest stone by brief rotation	Fix the second and the smallest stone by brief rotation	End of installation

<p><b>Parallel electrical connection 24V</b> Polarity: <b>RED cable + BLACK cable -</b></p>	<p><b>Connection:</b> Connector compliant with EN 60998-2-1 standards</p> <p>(FACSIMILE)</p>
---	--

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simple rule is not respected, the lighting source will be irretrievably damaged.

	<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 24V constant voltage		Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	--	---	--	--	--	--