



N° LED	W	Lm to the light source				R / V / B		
03	3.6	330	350mA	IP40	7° - 25° - 40°	-	-	2700K 3000K 4000K

Model	Description	Dimensions: Ø25 x 350mm	Rosette Ø50x2mm	Rosette Ø25
	<p>Aluminum Led body light for ceiling hanging. Finish: white RAL 9016 varnished, customized RAL, other materials on request. Single emission, transparent polycarbonate screen. It is provided with 2m black carrying cable 4mm diameter for the electrical connection. Indoor installation on any rigid surface. Fixing by two screws, not supplied by us, with specific rosette.</p>			

With rosette Ø50x2mm			With rosette Ø25mm		
Define the length of the suspension and fix the cable stopper by screwing the screw.	Do the electrical connection	Fix the rosette by screws with maximum diameter 4mm	Fix the rosette by screws with maximum diameter 4mm	Define the length of the suspension, fix the cable stopper by screwing the screw and do the electrical connection	Screw the socket to the rosette

<b>Series electrical connection 350mA SELV. Polarity: RED cable + BLACK cable -</b>	<b>Connection:</b> Connector compliant with EN 60998-2-1 standards

**ATTENTION:** Before starting all electrical connections, make sure that the power supply is not powered. If this simply rule is not respected, the lighting source will be irretrievably damaged.

<b>Compliant with European standards</b> (EMC, RoHS, Ecodesign and requirements specified in the Low Voltage Directive (LVD))	<b>CLASS III</b> Operating with SELV	<b>POWER SUPPLY</b> By remote power supply SELV OUTPUT 350mA constant current	Separate waste collection of electric and electronic equipment	<b>Made in Italy</b> Projected, manufactured and assembled in Italy
--	---	--	--	--